

- Space saving design for high density packaging
- Beryllium Copper multi-spring contact maintains retention after multiple insertions
- Ideal for mounting transistors, resistors, diodes, IC's and similar miniature components
- Custom micro jacks manufactured to your specifications
- Other platings available upon request


SPECIFICATIONS

Body: Brass, ASTM-B16 **Spring:** Beryllium Copper (QQ-C-533)


Plating:
Gold: .000005 per MIL-G-45204
RoHS (RoHS Compliant)

Tin/Lead: .000200 to .000300 per MIL-T-10727, Type 1 **ROHS** (Non-RoHS Compliant)

PLATING OPTIONS				
		CONTACT		
PLATING	BODY	SPRING	RoHS	
Gold/Gold	Gold	Gold	Compliant	
Tin/Tin	Tin/Lead	Tin/Lead	Non Compliant	
Tin/Gold	Tin/Lead	Gold	Non-Compliant	









RoHS	NON-RoHS			Mtg.
GOLD/GOLD	TIN/TIN	TIN/GOLD	L	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Length	Dia.
1411-1	1431-1	1420-1	.140 (3.6)	.042
1411-2	1431-2	1420-2	.170 (4.3)	(1.07)

.015 (.38) - .021 (.53) PIN - PRESS FIT



RoHS	NON-RoHS			Mtg.
GOLD/GOLD	TIN/TIN TIN/GOLD		L	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Length	Dia.
1412-1	1432-1	1468-1	.140 (3.6)	.040
1412-2	1432-2	1468-2	.170 (4.3)	(1.02)
1412-3	1432-3	1468-3	.282 (7.2)	(1.02)


.015 (.38) - .025 (.64) PIN - TAPER-FIT



RoHS	NON-RoHS			Mtg.
GOLD/GOLD	TIN/TIN TIN/GOLD		L	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Length	Dia.
1415-1	1435-1	1469-1	.160 (4.1)	.055
1415-2	1435-2	1469-2	.190 (4.8)	(1.40)


.015 (.38) - .025 (.64) PIN - SOLDER MOUNT






RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1413	1433	1470	.059 (1.50)

.015 (.38) - .025 (.64) PIN - SOLDER MOUNT




RoHS	NON-RoHS		Mtg.
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO. CAT. NO.		Dia.
1603	1606	1607	.052 (1.32)

.022 (.56) - .032 (.81) PIN - SOLDER MOUNT




KoHS	NUN-KOHS		Mtg.
GOLD/GOLD	TIN/TIN	TIN/GOLD	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1693	1694	1695	.063 (1.60)

.022 (.56) - .034 (.86) PIN - PRESS FIT




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN	TIN/GOLD	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1416	1436	1471	.067 (1.70)

.022 (.56) - .034 (.86) PIN - SOLDER MOUNT



RoHS	NON-	-RoHS	Mtg.
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1658	1659	1673	.065 (1.65)


.025 (.64) - .037 (.94) PIN - SOLDER MOUNT



RoHS	NON-RoHS			Mtg.
LD/GOLD	TIN/TIN TIN/GOLD		L	Hole
AT. NO.	CAT. NO.	CAT. NO.	Length	Dia.
626-1		1619-1		.062
626-2		1619-2		(1.57)
626-3	1614-3	1619-3	.155 (3.9)	(1.37)

.025 (.64) - .037 (.94) PIN - SOLDER MOUNT






(800) 221-5510 • kec@keyelco.com


RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
3590	3591	3592	.065 (1.65)

.025 (.64) - .037 (.94) PIN - PRESS FIT




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1697	1698	1699	.063 (1.60)

.032 (.81) - .046 (1.17) PIN - SWAGE MOUNT




RoHS		RoHS		Mtg.
GOLD/GOLD	TIN/TIN	TIN/GOLD	L	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Length	Dia.
1419-1	1439-1	1478-1	.062 (1.6)	.069
1419-2	1439-2	1478-2	.094 (2.4)	(1.75)



ROHS COMPLIANT ~ ISO 9001 CERTIFIED


MICRO JACKS

.032 (.81) - .046 (1.17) PIN - SOLDER MOUNT







.032 (.81) - .046 (1.17) PIN - PRESS-FIT



RoHS	NON-	Mtg.		
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole	
CAT. NO.	CAT. NO.	CAT. NO.	Dia.	
1443	1446	1473	.078 (1.98)	




.032 (.81) - .046 (1.17) PIN - SOLDER MOUNT



RoHS	NON-	Mtg.		
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole	
CAT. NO.	CAT. NO. CAT. NO.		Dia.	
1441	1444	1488	.076 (1.93)	

.032 (.81) - .046 (1.17) PIN - SOLDER MOUNT



RoHS	NON	Mtg.	
GOLD/GOLD	TIN/TIN	Hole	
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1674	1675	1676	.087 (2.21)


1445 1486 .032 (.81) - .046 (1.17) PIN - SOLDER MOUNT

.079 (2.0)




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN	Hole	
CAT. NO.	CAT. NO. CAT. NO.		Dia.
1677	1678	1679	.089 (2.26)

.032 (.81) - .046 (1.17) PIN - SOLDER MOUNT




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN	Hole	
CAT. NO.	CAT. NO. CAT. NO.		Dia.
1414	1434	1496	.089 (2.26)

.040 (1.02) - .050 (1.27) PIN - SOLDER MOUNT



KOHS		-KOHS	IVITG.
GOLD/GOLD	TIN/TIN	TIN/GOLD	Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1418	1438	1497	.104 (2.6)


.048 (1.22) - .064 (1.63) PIN - SOLDER MOUNT



KOHS	NUN-	Witg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1682	1683	1684	.102 (2.6)


.065 (1.65) - .082 (2.08) PIN - SOLDER MOUNT






RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO. CAT. NO.		Dia.
1641A	1641B	1641C	.122 (3.1)

.065 (1.65) - .082 (2.08) PIN - SOLDER MOUNT




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO.	CAT. NO.	Dia.
1687	1688	1689	.146 (3.7)


.084 (2.13) - .102 (2.6) PIN - PRESS-FIT




RoHS	NON-	Mtg.	
GOLD/GOLD	TIN/TIN TIN/GOLD		Hole
CAT. NO.	CAT. NO. CAT. NO.		Dia.
1640A	1640B	1640C	.138 (3.5)

.032 (.81) - .046 (1.17) PIN - CRIMP BARREL JACK







_	L V		.025 [0.63 SQUARE		
RoHS		NON-RoHS Mtg.			
GOLD/GOLD	TIN/TIN	TIN/GOLD	L	Hole	
CAT. NO.	CAT. NO.	CAT. NO.	Length	Dia.	
3501	3505	3504	.360 (9.2)	.057	

