
SURFACE MOUNT (SMT) COIN CELL ENCLOSURE CONTACTS


- · Contacts for Enclosure cases with self contained battery compartments
- · Design facilitates easy battery access, removal & installation
- Suitable for industrial and consumer product applications
- Spring contacts adjust to variations in battery diameter for a dependable connection
- Posititve and Negative contacts can be used as a design pair or individually on a PCB
- · Accomodates cell diameters from 12mm to 30mm



AVAILABLE ON TAPE AND REEL


MATERIAL: .006 (.15) Stainless Steel, Gold Plate (Flash)







CONTACT SELECTION GUIDE										
BATTERY Diameter	BATTERY Reference	CAT. NO. REFERENCE	MOUNTING DETAIL							
Accomodates 12mm to 16mm	CR1212, CR1216, CR1220, CR1612, CR1616, CR1620	120 (Pos) & 118 (Neg)	See page 38							
	CR1225, CR1625, CR1632	110 (Pos) & 118 (Neg)	See page 38							
Accomodates 20mm to 30mm	CR2012, CR2016, CR2020, CR2320, CR2412	120 (Pos) & 112 (Neg)	See page 38							
	CR2025, CR2032, CR2325, CR2330, CR2430, CR3032	110 (Pos) & 112 (Neg)	See page 38							
	CR2050, CR2335, CR2354, CR2430, CR2440, CR2450, CR2477, CR3048	122 (Pos) & 112 (Neg)	See page 38							






CAT. NO. 120TR Tape & Reel

Tape & Reel Spec's: 16mm wide, 8mm pitch, 13 inch reel, 3000 pieces per reel

POSITIVE

MEDIUM BATTERY HEIGHT 2.0mm to 3.2mm






CAT. NO. 110 Bulk

CAT. NO. 110TR Tape & Reel

Tape & Reel Spec's: 16mm wide, 8mm pitch, 13 inch reel, 2000 pieces per reel

TALL BATTERY HEIGHT 3.5mm to 7.7mm





CAT. NO. 122 Bulk


CAT. NO. 122TR Tape & Reel

Tape & Reel Spec's: 16mm wide, 8mm pitch, 13 inch reel, 1000 pieces per reel

NEGATIVE

BATTERY DIAMETER 12mm to 16mm






CAT. NO. 118 Bulk

CAT. NO. 118TR Tape & Reel

Tape & Reel Spec's: 24mm wide, 8mm pitch, 13 inch reel, 5000 pieces per reel

BATTERY DIAMETER 20mm to 30mm





CAT. NO. 112 Bulk

CAT. NO. 112TR Tape & Reel

Tape & Reel Spec's: 24mm wide, 8mm pitch, 13 inch reel, 5000 pieces per reel


SURFACE MOUNT (SMT) & THRU-HOLE (THM) NEGATIVE BATTERY CONTACTS



 Assures proper contact


Pad Lavout [1.57] MIN. SQR.

SMT COMPACT* .062 [1.54] .016 [.41] .030 [.76] DIA






AVAILABLE ON TAPE AND REEL



DWG. 2 MATERIAL: .010 (.25) Phospher Bronze

IIN-NICKEL PLAIE		WALLE IIN PLAIE					
CAT. NO	ON TAPE & REEL			DWG.	L	DIA.	TAPE & REEL SPECS
2991	2991TR	2981	2981TR	1	.368 (9.4)	.250 (6.4)	16mm wide, 8mm pitch, 1500/7 reel
2992	2992TR	2982	2982TR	1	.289 (7.4)	.186 (4.7)	16mm wide, 12mm pitch, 1000/7 reel
2993	2993TR	2983	2983TR	2	.625 (15.9)	-	24mm wide, 16mm pitch, 1000/13 reel





300 [7.6] .073 [1.9] DIA. (2) PLS

THM SNAP IN*

*Note: Cannot be used with Cat. No. 3028, 3029, 3032, 3038, 3042, 3026, 3078.

