

BATTERY INSULATORS (PULL TABS)

- Battery insulator will protect battery and circuitry during shipping and storage
- Insulator to be pulled out from product when it is time to activate
- Lettering and arrow provide intuitive markings for proper use
- Thin, flexible, strong insulator can be pulled from battery compartment even if the battery compartment is closed



MATERIAL: .007 Mineral Reinforced Polypropylene, white


CAT. NO. 117 1000 pieces per roll



MATERIAL: .005 Polyester, clear


CAT. NO. 121 (Bulk)

BUTTON CELL & "AAA"



MATERIAL: .007 Mineral Reinforced Polypropylene, white

CAT. NO. 111 1000 pieces per roll



MATERIAL: .005 Polyester, clear


CAT. NO. 119 (Bulk)

POLARITY INDICATING LABEL




CAT. NO. 58

- No gluing or wetting needed
- Pressure sensitive adhesive back
- Economical
- Adheres to all surfaces



INSULATED POLARIZING WASHERS

- Prevents improper connection of battery which may cause damage to electronic equipment
- Washers hold securely when snapped over eyelets
- Used on our standardized battery holders
- For "AA", "C" & "D" cells.





MATERIAL: Molded Polyethylene

CAT. NO. 59 (RED)


CAT. NO. 60 (BLACK)

COIN CELL ENCLOSURE CONTACT LAYOUTS






CAT. NO.	BATTERY REFERENCE	L
120 & 118	CR1216, CR1220	.178 (4.5)
	CR1612, CR1616, CR1620	.256 (635)




	CAT. NO.	BATTERY REFERENCE	L
4	110 & 118	CR1225	.213 (5.4)
110 & 110	CR1632	.291 (7.4)	



CAT. NO.	BATTERY REFERENCE	L
	CR2012, CR2016, CR2020	.336 (8.5)
120 & 112	CR2320	.395 (10.0)
	CR2412	.414 (10.5)



CAT. NO.	BATTERY REFERENCE	L
110 & 112	CR2025, CR2032	.370 (9.4)
	CR2325, CR2330	.429 (10.9)
	CR2430	.448 (11.4)
	CR2032	.567 (14.4)



CAT. NO.	BATTERY REFERENCE	L
	CR2354	.429 (10.9)
120 & 112	CR2450, CR2477	.448 (11.4)
	CR3032	.567 (14.4)