These easy-to-mount, multipurpose screw type terminals are a practical, low-cost alternative to PC screw type edge connectors, barrier blocks, terminal boards and terminal strips. Steadfast and easy to install, will accommodate solid or stranded wire, crimp type terminals or lugs. Multi-placement of these low-profile terminals make them ideally suited for high density packaging. Supplied unassembled or with screw installed and captivated.

PRINCIPAL FEATURES

- Low profile
- Stable, no-rock design with exclusive anti-rotational feature
- · Easily mounts with four legs into pre-drilled or punched holes
- Accepts #14-22 AWG solid or stranded wire, crimp type terminals or lugs
- Ideally suited for high-density packaging
- · Available in horizontal or vertical mounting
- · Space-saving and time saving
- · Easy accessibility for PC board testing
- · Binding screw is positioned above board level to avoid wicking during wave soldering
- · Terminals are made of Brass with Tin Plate
- · Supplied with a combination drive 6-32 binding head screw

CAT. NO. COLOR SUFFIX Ex: XXXX

COLOR SELECTION:

Select desired screw terminal and add color suffix to the screw terminal Cat. No.


| HEAD COLOR | SUFFIX |
|------------|--------|
| RED | -2 |
| BLACK | -3 |
| WHITE | -4 |
| BLUE | -5 |
| GREEN | -6 |
| YELLOW | -7 |
| NICKEL | none |



7692-2

SNAP-IN PC MOUNT

Color coded screws available (add color screw suffix to Cat. No.)



MINI

CAT. NO. 7779 (No Screw Supplied)

CAT. NO. 7690 (Screw Supplied Unassembled)

CAT. NO. 7692 (Screw Installed & Captivated)

HORIZONTAL TYPE

SPECIFICATIONS

Rated: 15 Amps

Terminal:


.032 (.81) Brass, Matte Tin Plate

Binding Head Screw:

Brass, Nickel Plate



Color coded screws available (add color screw suffix to Cat. No.)





PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)


CAT. NO. 7781 (No Screw Supplied)


CAT. NO. 8190 (Screw Supplied Unassembled)

CAT. NO. 7700 (Screw Installed & Captivated)



SNAP-IN PC MOUNT





SPECIFICATIONS

Rated: 15 Amps

.032 (.81) Brass, Matte Tin Plate **Binding Head Screw:**

Brass, Nickel Plate

6-32 x .250 [6.3] L. SCREW .450 [11.5] 45 REF. .125 - [3.2] REF. .037 [1.0] .295 [7.5] .130 [3.3] .190 [4.9]

45°



PC MOUNT

Color coded screws available (add color screw suffix to Cat. No.)




CAT. NO. 7783 (No Screw Supplied)

CAT. NO. 8189 (Screw Supplied Unassembled) CAT. NO. 7702 (Screw Installed & Captivated)



SNAP-IN PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)



CAT. NO. 7780 (No Screw Supplied)

CAT. NO. 7774 (No Screw Supplied)

CAT. NO. 7773 (Screw Supplied Unassembled)

CAT. NO. 7691 (Screw Supplied Unassembled)


CAT. NO. 7693 (Screw Installed & Captivated)

VERTICAL TYPE SPECIFICATIONS

Rated: 15 Amps Terminal: .032 (.81) Brass, Matte Tin Plate **Binding Head Screw:** Brass, Nickel Plate



Color coded screws available (add color screw suffix to Cat. No.)





PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)

CAT. NO. 7782 (No Screw Supplied)

CAT. NO. 8191 (Screw Supplied Unassembled)

CAT. NO. 7701 (Screw Installed & Captivated)




(800) 221-5510 • kec@keyelco.com





· Color coded screws available (add color screw suffix to Cat. No.)



SPECIFICATIONS Rated: 15 Amps

Terminal: .032 (.81) Brass, Matte Tin

Plate Binding Head Screw: Brass, Nickel Plate



.197 [5.0]

.197 [5.0]



Color coded screws available (add color screw suffix to Cat. No.)



.062 [1.57] DIA. (4) PLS

.059 [1.5]

(4) PLS

.187 [4.7] (2) PLS

CAT. NO. 7784 (No Screw Supplied)

CAT. NO. 8198 (Screw Supplied Unassembled)

CAT. NO. 7778 (Screw Installed & Captivated)

Mounting Detail .312 [7.9] Ó .067 [1.7] DIA

SPECIFICATIONS Rated: 15 Amps

CAT. NO. 7785 (No Screw Supplied)

CAT. NO. 8195 (Screw Supplied Unassembled) CAT. NO. 7775 (Screw Installed & Captivated)


VERTICAL TYPE

Binding Head Screw: Brass, Nickel Plate




PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)




CAT. NO. 7789 (No Screw Supplied)

CAT. NO. 7697 (Screw Supplied Unassembled) CAT. NO. 7699 (Screw Installed & Captivated)





.276 [7.0] 1-0 .073 [1.85] DIA. (4) PLS



HEAVY DUTY

CAT. NO. 7791 (No Screw Supplied) CAT. NO. 8174 (Screw Supplied Unassembled)






341 [8.7] 0 .073 [1.85] DIA

8196

HORIZONTAL





CAT. NO. 7801 (No Screw Supplied)

CAT. NO. 8166 (Screw Supplied Unassembled)

30 AMP - HEAVY DUTY **SPECIFICATIONS**

Rated: 30 Amps Terminal: .045 (1.14) Brass, Matte Tin Plate Screw: Stainless Steel






VERTICAL

CAT. NO. 7787 (No Screw Supplied)

CAT. NO. 8196 (Screw Supplied Unassembled)

30 AMP



Tel (516) 328-7500 • Fax (516) 328-1080

(800) 221-5510 • kec@keyelco.com

SPECIFICATIONS

Rated: 30 Amps

Terminal: .032 (.81) Brass, Matte Tin Plate Binding Head Screw: Brass, Nickel Plate

CAT. NO. 8197 (Screw Supplied Unassembled)

CAT. NO. 8199 (Screw Installed & Captivated)

.310 [7.9] __.250 [6.3] .210 [5.3] Mounting Detail .394 [10.0] .394 [10.0] O Ó CAT. NO. 7786 (No Screw Supplied) [5.0] Ö .076 [1.93] DIA. (6) PLS

COLOR CODED GUIDE

COLOR SELECTION:

Select desired screw terminal and add color suffix to the screw terminal Cat. No.

| HEAD COLOR | SUFFIX |
|------------|--------|
| RED | -2 |
| BLACK | -3 |
| WHITE | -4 |
| BLUE | -5 |
| GREEN | -6 |
| YELLOW | -7 |
| NICKEL | none |

CAT. NO. COLOR SUFFIX Ex: XXXX



Refer to page 69 for color screws only

SEMS SCREW TERMINALS


SPECIFICATIONS


Terminal: .032 (.81) Brass, Matte Tin Plate Screw & Washer: Steel, Nickel Plate

SEMS Screw Terminals provide quick and secure attachment of wire leads. SEMS screw has captivated, free spining lock washer, eliminated twisting of wire when tightening lead to terminal. Washer will rise with head of screw when unscrewed.









SEMS SCREW ONLY










| CAT. NO. 8189-SEMS | (Screw Supplied Unassembled) |
|--------------------|--------------------------------|
| CAT. NO. 7702-SEMS | (Screw Installed & Captivated) |

| CAT. NO. | THREAD | LENGTH |
|----------|--------|------------|
| 9920 | 6-32 | .250 (6.4) |
| 9923 | М3 | .188 (4.8) |













| 6-32 THREAD | | M3 THREAD |
|-------------|----------------------------|------------------|
| CAT. NO. | | CAT. NO. |
| 7681-SEMS | Screw Supplied Unassembled | 7698-SEMS |
| 7693-SEMS | No Screw Supplied | 7696-SEMS |

| 6-32 THREAD CAT. NO. | | M3 THREAD CAT. NO. |
|----------------------|----------------------------|--------------------|
| 8191-SEMS | Screw Supplied Unassembled | 7771-SEMS |
| 7701-SEMS | No Screw Supplied | 7772-SEMS |






| 6-32 THREAD | | M3 THREAD |
|------------------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7690-SEMS | Screw Supplied Unassembled | 7699-SEMS |
| 7692-SEMS | Screw Installed & Captivated | 7695-SEMS |






| 6-32 THREAD | | M3 THREAD |
|-------------|----------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 8190-SEMS | Screw Supplied Unassembled | 7761-SEMS |
| 7700-SEMS | No Screw Supplied | 7762-SEMS |











CAT. NO. 8195-SEMS (Screw Supplied Unassembled) CAT. NO. 7775-SEMS (Screw Installed & Captivated)

CAT. NO. 8198-SEMS (Screw Supplied Unassembled) CAT. NO. 7778-SEMS (Screw Installed & Captivated)









CAT. NO. 8197-SEMS (Screw Supplied Unassembled) CAT. NO. 8199-SEMS (Screw Installed & Captivated)

KEYSTONE RoHS COMPLIANT - ISO 9001 CERTIFIED

Tel (516) 328-7500 • Fax (516) 328-1080

These easy-to-mount, multipurpose screw type terminals are a practical, low-cost alternative to PC screw type edge connectors, barrier blocks, terminal boards and terminal strips. Steadfast and easy to install, will accommodate solid or stranded wire, crimp type terminals or lugs. Multi- placement of these low-profile terminals make them ideally suited for high density packaging. Supplied unassembled or with screw installed and captivated.

PRINCIPAL FEATURES

- · Stable, no-rock design with exclusive anti-rotational feature
- Easily mounts with four legs into pre-drilled or punched holes
- Accepts #14-22 AWG solid or stranded wire, crimp type terminals or lugs
- · Ideally suited for high-density packaging
- · Easy accessibility for PC board testing
- Binding screw is positioned above board level to avoid wicking during wave soldering
- · All dimensions appear in millimeters

RFD BLACK WHITE -4 BLUE **COLOR SELECTION:** GREEN -6 Select desired screw terminal YELLOW -7 and add color suffix to the NICKEL none screw terminal Cat. No.

HEAD COLOR



Refer to page 69 for color screws only

HORIZONTAL TYPE



SNAP-IN PC MOUNT

 Color coded screws available (add color screw suffix to Cat. No.)


| | | | \mathbb{Q} | | |
|---|--------------------|----------|--------------|----------------|-------------|
| (| 6.00 LONG SCREW | $Z \pm$ | <u> </u> | ← 11.50 | - |
| | | 7.11 | a | | 7.90 |
| | ∛ | } | | Ä | 5.10 |
| | 6.60 | - | 1.52 — | 5.0 | _ |
| ` | | | | | |

SPECIFICATIONS

Rated: 15 Amps

Terminal: .81 Brass, Matte Tin Plate

Screw: Brass, Nickel Plate



· Color coded screws available (add color screw suffix to Cat. No.)

| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7760 | No Screw Supplied | 7764 |
| 7761 | Screw Supplied Unassembled | 7765 |
| 7762 | Screw Installed & Captivated | 7766 |

M3 THREAD M4 THREAD CAT. NO. CAT. NO. No Screw Supplied 7790 Screw Supplied Unassembled 7793 7695 Screw Installed & Captivated 7794

VERTICAL TYPE

Mounting Detail

Ó

√0

5.00 LO

1.85 DIA. HOLE (4) PLS



SNAP-IN PC MOUNT

 Color coded screws available (add color screw suffix to Cat. No.)

| 6.00 LOI SCRE | |
|------------------|----------------------|
| 7.00 | 8.00 6.45 1.52 |

M4

6.35

1.52

-12 88

10.00

11.68

Mounting Detail

7.00 O D 000

1.93 DIA. HOLE -/

10.00


M4 x 6.00 L SCREW

SPECIFICATIONS

Rated: 15 Amps

Terminal: .81 Brass, Matte Tin Plate

Screw: Brass, Nickel Plate





PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)

| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7788 | No Screw Supplied | 7795 |
| 7698 | Screw Supplied Unassembled | 7796 |
| 7696 | Screw Installed & Cantivated | 7797 |

| 7.00 7.00 5.00 |
|------------------------------|
| 10 9 |
| 1.85 DIA. HOLE —/ (4) PLS |
| |

Mounting Detail

| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7770 | No Screw Supplied | 7767 |
| 7771 | Screw Supplied Unassembled | 7768 |
| 7772 | Screw Installed & Captivated | 7769 |

30 AMP - VERTICAL TYPE

SNAP-IN PC MOUNT

· Color coded screws available (add color screw suffix to Cat. No.)

SPECIFICATIONS


Rated: 30 Amps

Terminal: .81 Brass, Matte Tin Plate Screw: Brass, Nickel Plate


| CAT. NO. | |
|----------|------------------------------|
| 7798 | No Screw Supplied |
| | Screw Supplied Unassembled |
| 7800 | Screw Installed & Captivated |
| | |

PRINCIPAL FEATURES

- · Compact, heavy duty design
- . Six snap-in legs for total stability
- Serrated top surface secures connection



M5



SPECIFICATIONS Rated: 30 Amps

Terminal: 1.14 Brass, Matte Tin Plate Screw: Brass, Nickel Plate

| | CAT. NO. | |
|--|----------|----------------------------|
| | 7807 | No Screw Supplied |
| | 7808 | Screw Supplied Unassembled |



SNAP-IN PC MOUNT



Tel (516) 328-7500 • Fax (516) 328-1080

